

PILLOW CASES

(For additional, faster methods for serging, see separate instruction sheet)

FABRIC: cotton, cotton/poly, cotton flannel 44/45" wide

Body: $\frac{3}{4}$ yd, hem $\frac{1}{4}$ yd coordinating, decorative trim optional: lace, piping, seam binding, fabric, etc. LABEL

ROLLED OR HOT DOG, METHOD

Roll body into 44" tube WRONG SIDE OUT. If using directional print, roll from TOP OF PRINT, leaving bottom edge of print free.

Place hem right side up. If using directional print for hem, see note at bottom.

Place free end of tube along one edge of hem. If adding decorative trim. Place it on top of both layers, aligning edges. Carefully fold free end of hem over the roll and align and pin the edge. Straight stitch or serge.

Pull roll from inside tube. Press.

TO FINISH

SERGE ONLY Fold right sides together, serge side and bottom, catching label in seam at hem.

Turn and Press

STRAIGHT STITCH. Fold wrong sides together, sew $\frac{1}{4}$ " seam on side and bottom. Turn. Lightly press seams. Now with right sides together, sew $\frac{1}{2}$ " seam on side and bottom, catching label at hem. This makes a nice sturdy seam with no raw edges. Turn and press.

NOTE. If using directional print for HEM, place rolled tube so free end is toward you. Place the hem right side up along free end of roll so both prints are running in same direction. Now, without turning any fabric, slide hem under tube. Or lift roll and place on edge of hem closest to you. They will be right sides together. Align edges, place any decorative trim on top of roll along edge; fold free end of hem over the roll, align edges and pin. Straight stitch or serge. Pull roll from inside tube, press, and finish as above.