

## SERGED PILLOW CASES

### SELF HEM, ONE PIECE

FABRIC: Cotton jersey knit, or cotton, cotton flannel. 1 yard 44/45" LABEL

SERGE along one side of the 44" width. If working with directional print fabric, serge the edge at the BOTTOM of the print.

FOLD right sides together and SERGE together side and UNSerged end.

TURN DOWN open end 5" and stitch to form hem.

Turn and press.

**TWO PIECES**  $\frac{3}{4}$  yard 44" fabric;  $\frac{1}{4}$  yard coordinating 44" fabric, decorative piping, lace, etc.

Fold  $\frac{1}{4}$  yd (hem) in half long way and press, right side out.

Place raw edges of hem along 44" edge of larger piece, right sides together, and serge together. If adding a decorative trim, insert between hem and body. Press seam toward body of case.

Fold right sides together; serge side and bottom, catching LABEL in side seam at hem.

Turn and press.

### **NOTE on use of directional prints**

when using directional print for **body**, sew hem to **bottom** of print.

when using directional print for **hem**, open and lay flat along 44" edge so that print on both pieces is going in same direction, i.e. match the print. Then flip hem onto body, right sides together, fold hem, and serge.

Print direction on finished case should be viewed properly from side of bed.